

GUIDE SPECIFICATION

Boyd Aluminum Manufacturing Company
P.O. Box 1565
3248 E. Division Street
Springfield, MO 65801-1565
800-737-2800
417-862-1232 fax
boydaluminum.com

Boyd Architectural Muntin Systems

1. Components

- a. Applied Muntins: Prefabricated simulated divided lite grid assembly with perimeter surround; designed to be adhered and fastened to the storefront/curtain wall framing members and glazing.
 - i. Material: Extruded Aluminum
 - ii. Profile: Manufacturer's standard, as detailed on drawings
 - iii. Finish:
 - iv. Mounting: Anchor pins at perimeter. Tape applied perimeter surround.
 - v. Pin Hole Filler: Manufacturer's standard, matching color of muntin grid.
 - vi. Manufacturers:
 1. Boyd Aluminum; Boyd Architectural Muntin Systems:
www.boydaluminum.com

Boyd Manufacturing Company has prepared this guide specification in printed and electronic media, as an aid to specifiers in preparing written construction documents for commercial aluminum windows. For specification assistance on specific product applications, please contact our offices. Boyd Aluminum Manufacturing Company reserves the right to modify these specifications and details at any time. Updates to these guide specifications and details will be posted to our web site and/or in printed matter as they occur. Boyd Aluminum Manufacturing Company makes no expressed or implied warranties regarding content, errors, or omissions in the information presented.

2/22/21

800-737-2800
boydaluminum.com